

1310nm~1320nm 1W Fiber Coupled Diode Laser Module | PD Optional | Aiming Beam Optional
1310nm 1W |2-PIN Package| 105um 200um 400um Fiber Core| High Power LD
WSLX-1310-001-M-H2
Wavespectrum Laser Group
www.wavespectrum-laser.com

PARAMETER	SYMBOL	VALUE	UNIT
Reverse Voltage	V_r	2.0	V
Operating Temperature	T_{op}	+10 ~ +30	°C
Storage Temperature	T_{stg}	-20 ~ +80	°C
Lead soldering temperature (10 sec.)	T_{is}	260	°C

Features:

- 1310nm
- 2-Pin package
- PD Optional
- TEC Cooling Optional

Applications:


- Medical Laser Treatment
- Others


Specifications
WSLX-1310-001-M-H2

	Mini	Type	Max
Center Wavelength@25°C	1310nm±30nm		
Spectral Width (FWHM)	----	8nm	----
Output Power	----	1W	----
Temperature Coefficient of Wavelength	----	0.7nm / °C	----
Threshold Current (Typ.)	----	0.4A	0.7A
Operating Current (Typ.)	----	3.3A	3.5A
Operating Voltage	----	1.4V	1.6V
Recommended Case Temperature	25°C		
Fiber Core Diameter	105um (200um, 400um Optional)		
Fiber Numerical Aperture	0.22 (0.37N.A. Optional)		
Fiber Length	>80cm		
Connector Type	SMA905/ST/FC		
Package Style	2-Pin		



2-Pin Package View



Wavespectrum offer **Customized 1310nm Fiber Coupled LD.**

- Customized Output Power
- Customized Fiber Core
- **Dual-Wavelength or Tri-Wavelength Module Optional**
 (such as 2W@1310nm+350mW@635nm)

More information please contact us:

Website: www.wavespectrum-laser.com , en.wavespectrum-laser.com.cn

Email: Info@wavespectrum-laser.com , sales@wavespectrum-laser.com

Electrically shorten LD module and store in non-extreme conditions.

Suggest using the constant current power supply.



Wavespectrum Laser Group
www.wavespectrum-laser.com
sales@wavespectrum-laser.com

