

T Series TO-Can **15XXnm 50mW**

Single mode, Continuous Wave (CW)



Optical Electrical Characteristics **

Parameter	Unit					
Wavelength	nm					
Operating Power	mW					
Operating Current*	mA					
Operating Voltage	V					
Threshold Current	mA					
Slope Efficiency	W/A					
Vertical Far Field @FWHM	deg ^o					
Horizontal Far Field @FWHM	deg ^o					

50mW						
Тур	Max					
1560	1570					
50	-					
140	200					
1.6	2.0					
30	40					
0.45	•					
26	-					
8	10					

Absolute Maximum Ratings

•					
Parameter	Unit	Condition	Min	Тур	Max
Operational Temperature***	оС	CW	-20	25	50
Storage Temperature	οС		-40	25	85

^{*} Please note that CW lasers may be damaged by excessive drive current or switching transients.

5.6 mm (M5)

M5-15XX-0050-XXXX

Features &Options

- Compact package with small footprint.
- Hermetically sealed to deal with harsh conditions.
- Single spatial mode
- Photo diode integrated into the package.
- Low, Standard and High antireflective coating options available.

This datasheet is for general reference only. Specifications are subject to change without notice. Product subject to availability. Visit sheaumann.com or contact sales@sheaumann.com for more information on products and services.



Safety Warning

Laser light emitted from any laser diode is invisible and may be harmful to the human eye. Avoid looking directly into the laser aperture when the device is in operation.

The use of optical instruments with this product will increase eye hazard.

The primary cause of diode failure is unexpected electrostatic discharge. To help prevent device failures, the user should always wear an ESD wrist strap, ground all applicable work surfaces and follow anti-static techniques when handling

Operation Consideration

Operating the laser beyond the limits of the provided specifications may result in device failure or a safety hazard and will void warranty. Devices must be passively or actively cooled in accordance with the provided specifications. Failure to comply with heatsinking requirements may result in device failure.

Due to the delicate nature of laser diodes, Sheaumann offers a limited warranty for all products. Please refer to our Terms and Conditions for full details.

Compliance Notice

These products are intended solely as a component of an electronic product and are not certified in accordance with IEC 60825-1 or 21 CFR 1040.10/21 CFR 1040.11. These products are subject to Export Administration Regulations (EAR) and will require a Destination Control Statement or End User Agreement for each sales order.











+1 508.970.0600

sheaumann.com



^{**} Data is based on CW operation at 25°C.

^{***} Device degradation accelerates with increased temperature.